



HI - MILER CXG **(LIGHT TRUCK)**

Jarak tempuh lebih unggul dengan traksi maksimum untuk *on* dan *off road*.

Tahan terhadap berbagai kondisi jalan.

Mempermudah pelepasan batu, mencegah terpotong dan terkikis.

HI - MILER CXG (LIGHT TRUCK)

Fitur	Keunggulan
Anti-selip	Performa jarak tempuh dan traksi yang lebih baik.
Sudut kerapatan <i>groove</i> semakin optimal	Mempermudah terlepasnya batu, melindungi dari terpotong dan terkikis
Desain telapak yang unik	Traksi yang unggul untuk <i>on</i> dan <i>off road</i> .
Konstruksi <i>belt</i> pada ban <i>bias</i>	Menambah ketahanan terhadap benturan.

SPESIFIKASI TEKNIS

Size	PR	Recommended Rim Width inch	Approved Rim Width inch	Size Factor	Minimum Dual Spacing mm	Avg NSD mm	Inflated Dimension	
							Overall Width mm	Overall Diameter mm
6.40-13	8	4.0	4.0, 4.5	812	214	12.4	172	640
6.50-14	8	4.5	4.5J, 5J	877	220	9.3	175	702

TABEL TEKANAN / BEBAN

Size	PR	Load Information		Inflation Information			
		Max Load Single kg	Max Load Dual kg	Max Cold Inflation Single		Max Cold Inflation Dual	
				psi	kPa	psi	kPa
6.40-13	8	710	670	65	450	65	450
6.50-14	8	780	795	62	430	62	430

APLIKASI

Application	Steer Axle	Drive Axle	All Positions
Mixed Service			✓
Off the Road			✓

